



HPE 1810 Switch Series



Key features

- Customized operation using intuitive Web interface
- Flexible connection and deployment options
- Layer 2 operation at wire speeds
- Fanless design for quiet operation
- Limited lifetime warranty

Product overview

HPE 1810 Switch Series devices are smart-managed, fixed-configuration Gigabit Ethernet and Fast Ethernet Layer 2 switches designed for small businesses looking for key features in an easy-to-administer solution.

The series includes 8- and 24-port Gigabit Ethernet and Fast Ethernet models and a 48-port Gigabit Ethernet switch. Some models include SFP ports for fiber connectivity and some are fanless, making them ideal for office deployments. All HPE 1810 Switch Series support flexible installation options, including mounting on walls, under tables, or on desktops. The 8-port Gigabit Ethernet model can be powered by an upstream Power over Ethernet (PoE) switch for environments where no line power is available.

Customizable features include VLANs, Spanning Tree, and link aggregation trunking; 8- and 24-port switches offer Rapid Spanning Tree Protocol (RSTP) and DSCP QoS policies. The 8- and 24-port models also include the latest energy-saving capabilities, including Energy Efficient Ethernet (EEE) and idle-port power down. HPE 1810 switches are covered by a limited lifetime warranty.

Features and benefits

Connectivity

- Auto-MDI/MDIX

Automatically adjusts for straight-through or crossover cables on all ports

- Packet storm protection

Protects against broadcast, multicast, or unicast storms with user-defined thresholds

- IEEE 802.3af PoE-powered device option

Obtains power provided by a standard PoE device connected to Port 1; deploys the switch wherever an Ethernet cable can reach as a power outlet is not needed (8-port GbE model only)

- SFP ports for fiber connectivity

Provides fiber connections for uplinks and other connections across longer distances than copper cabling can support; “true” SFP ports operate in addition to available copper Ethernet ports, providing a higher total number of available ports vs. “combo” ports, which are either a copper or fiber connection

Performance

- Half- or full-duplex auto-negotiating capability on every port doubles the throughput of every port

- Link aggregation (trunking)

Brings together groups of ports automatically using Link Aggregation Control Protocol (LACP) or, manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks; 8-port models have four trunks of four links each, the 24-port models have eight trunks of four links each, and HPE 1810-48G Switch has 16 trunks of eight links each

Quality of service (QoS)

- Traffic prioritization (IEEE 802.1p)

Allows real-time traffic classification with eight priority levels mapped to four queues

- IEEE 802.1p prioritization with DSCP

Delivers data from the switch to devices based on the priority and type of traffic using Differentiated Services Code Point (DSCP); available only with v2 switch models

- Broadcast control

Allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

Layer 2 switching

- VLAN support and tagging

Supports up to 64 port-based VLANs and dynamic configuration of IEEE 802.1Q VLAN tagging, providing security between workgroups

- Jumbo packet support

Improves the performance of large data transfers; supports frame size of up to 9,220 bytes

Resiliency and high availability

- IEEE 802.1D Spanning Tree Protocol (STP) and IEEE 802.1W Rapid Spanning Tree Protocol (RSTP)

Provide redundant links while preventing network loops; available only with v2 switch models

Security

- Secure Sockets Layer (SSL)

Encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch

- Automatic denial-of-service protection
Monitors six types of malicious attacks and protects the network by blocking the attacks
- Management password
Provides security so that only authorized access to the Web browser interface is allowed

Ease of use

- Locator LED (switch)
Allows users to set the locator LED on a specific switch to either turn on, blink, or turn off; simplifies troubleshooting by making it easy to locate a particular switch within a rack of similar switches
- Comprehensive LED display with per-port indicators
Provides an at-a-glance view of status, activity, speed, and full-duplex operation

Flexibility

- Flexible installation
Allows mounting on wall, desktop, or under-table
- Rack mountable (24- and 48-port models)
Offers a rack-mounting option with included hardware
- Kensington lock slot
Allows switches to be physically secured in open-space deployments

Management

- Simple Web management
Allows easy management of devices by nontechnical users with its intuitive Web GUI
- Secure Web GUI
Provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- SNMPv1, v2c
Enable devices to be discovered and monitored from an SNMP management station
- Dual flash images
Provide independent primary and secondary operating system files for backup while upgrading
- Port mirroring
Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)
Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications

Additional information

- Energy savings
Utilizes Energy Efficient Ethernet (EEE) IEEE 802.3az standard for lower power consumption; available only with v2 switch models
- Green IT and power
Places inactive ports automatically in low-power mode and its LED in power-down mode, to conserve energy
- Green initiative support
Provides support for RoHS and WEEE regulations

Warranty and support

- Limited Lifetime Warranty
See hpe.com/networking/warrantysummary for warranty and support information included with your product purchase.

HPE 1810 Switch Series



SPECIFICATIONS

HPE 1810-24G v2 Switch (J9803A)

HPE 1810-48G Switch (J9660A)

HPE 1810-8 v2 Switch (J9800A)

I/O ports and slots

24 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

2 SFP 100/1000 Mbps ports

Supports a maximum of 24 autosensing 10/100/1000 ports plus 2 SFP ports

48 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

4 SFP 100/1000 Mbps ports

Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 SFP ports

7 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

1 RJ-45 autosensing 10/100/1000 port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

Supports a maximum of 7 autosensing 10/100 ports plus 1 autosensing 10/100/1000 ports

Physical characteristics

Dimensions

12.99(w) x 6.81(d) x 1.73(h) in
(32.99 x 17.3 x 4.39 cm) (1U height)

17.4(w) x 9.75(d) x 1.75(h) in
(44.2 x 24.77 x 4.45 cm) (1U height)

7.93(w) x 4.65(d) x 1.73(h) in
(20.14 x 11.81 x 4.39 cm) (1U height)

Weight

2.54 lb (1.15 kg)

6.31 lb (2.86 kg)

0.77 lb (.35 kg)

Memory and processor

128 MB RAM, 8 MB flash;
packet buffer size: 512 KB

64 MB RAM, 8 MB flash;
packet buffer size: 1.5 MB

128 MB RAM, 8 MB flash;
packet buffer size: 512 KB

Mounting and enclosure

Mounts in an EIA-standard 19 in. telco rack (hardware included); horizontal surface, wall, and under-table mounting

Mounts in an EIA-standard 19 in. telco rack (hardware included); wall, desktop, tabletop, and under-table mounting

wall, desktop, and under-table mounting

Performance

100 Mb Latency

< 3.3 μ s (64-byte packets)

< 8.4 μ s (64-byte packets)

< 3.3 μ s (64-byte packets)

1000 Mb Latency

< 2.2 μ s (64-byte packets)

< 3.2 μ s (64-byte packets)

Throughput

up to 38.7 Mpps

up to 77.4 Mpps

up to 2.5 Mpps

Switching capacity

52 Gbps

104 Gbps

3.4 Gbps

MAC address table size

8000 entries

16000 entries

8000 entries

Environment

Operating temperature

32°F to 104°F (0°C to 40°C)

32°F to 113°F (0°C to 45°C)

32°F to 104°F (0°C to 40°C)

Operating relative humidity

15% to 95% @ 104°F (40°C)

15% to 95% @ 104°F (40°C),

15% to 95% @ 104°F (40°C)

Nonoperating/Storage temperature

-40°F to 158°F (-40°C to 70°C)

noncondensing

-40°F to 158°F (-40°C to 70°C)

Nonoperating/Storage relative humidity

15% to 95% @ 140°F (60°C)

-40°F to 158°F (-40°C to 70°C)

15% to 95% @ 140°F (60°C)

Altitude

up to 10,000 ft (3 km)

15% to 90% @ 149°F (65°C),

up to 10,000 ft (3 km)

Acoustic

Power: 0 dB no fan

noncondensing
up to 10,000 ft (3 km)
Power: 22 dB single fan

Power: 0 dB no fan

Electrical characteristics

Frequency

50/60 Hz

50/60 Hz

50/60 Hz

Maximum heat dissipation

100 - 127 / 200 - 240 VAC

204 BTU/hr (215.22 kJ/hr)

AC voltage

100 - 127 / 200 - 240 VAC

100 - 127 / 200 - 240 VAC

100 - 240 VAC

Current

.4/3 A

0.9/0.5 A

.5 A

Maximum power rating

22 W

60 W

4.8 W

Notes

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

SPECIFICATIONS	HPE 1810-24G v2 Switch (J9803A)	HPE 1810-48G Switch (J9660A)	HPE 1810-8 v2 Switch (J9800A)
Safety	UL 60950-1; IEC 60950; EN 60950	CSA 22.2 No. 60950; EN 60950/ IEC 60950; UL 60950	UL 60950-1; IEC 60950; EN 60950
Emissions	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4	EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4
Immunity			
ESD	IEC 61000-4-2	IEC 61000-4-2	IEC 61000-4-2
Radiated	IEC 61000-4-3	IEC 61000-4-3	IEC 61000-4-3
EFT/Burst	IEC 61000-4-4	IEC 61000-4-4	IEC 61000-4-4
Surge	IEC 61000-4-5	IEC 61000-4-5	IEC 61000-4-5
Conducted	IEC 61000-4-6	IEC 61000-4-6	IEC 61000-4-6
Power frequency magnetic field	IEC 61000-4-8	IEC 61000-4-8	IEC 61000-4-8
Voltage dips and interruptions	IEC 61000-4-11	IEC 61000-4-11	IEC 61000-4-11
Harmonics	EN 61000-3-2	EN 61000-3-2	EN 61000-3-2
Flicker	EN 61000-3-3	EN 61000-3-3	EN 61000-3-3
Management	Web browser	Web browser	Web browser
Notes	Use only supported genuine HPE mini-GBICs with your switch.	Use only supported genuine HPE mini-GBICs with your switch.	Use only supported genuine HPE mini-GBICs with your switch.
Services	Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.	Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

HPE 1810 Switch Series



HPE 1810-24 v2 Switch (J9801A)



HPE 1810-8G v2 Switch (J9802A)

SPECIFICATIONS

I/O ports and slots

22 RJ-45 autosensing 10/100 ports
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

2 RJ-45 autosensing 10/100/1000 ports
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

2 SFP 100/1000 Mbps ports

Supports a maximum of 22 autosensing 10/100 ports plus 2 autosensing 10/100/1000 ports plus 2 SFP ports

8 RJ-45 autosensing 10/100/1000 ports
(IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only

Supports a maximum of 8 autosensing 10/100/1000 ports

Physical characteristics

Dimensions

12.99(w) x 6.81(d) x 1.73(h) in (32.99 x 17.3 x 4.39 cm)
(1U height)

7.93(w) x 4.65(d) x 1.73(h) in (20.14 x 11.81 x 4.39 cm)
(1U height)

Weight

2.2 lb (1 kg)

0.84 lb (.38 kg)

Memory and processor

128 MB RAM, 8 MB flash; packet buffer size: 512 KB

128 MB RAM, 8 MB flash; packet buffer size: 512 KB

Mounting and enclosure

Mounts in an EIA-standard 19 in. telco rack (hardware included); horizontal surface, wall, and under-table mounting

wall, desktop, and under-table mounting

Performance

100 Mb Latency
1000 Mb Latency
Throughput
Switching capacity
MAC address table size

< 3.4 μ s (64-byte packets)

up to 9.2 Mpps
12.4 Gbps
8000 entries

< 3.3 μ s (64-byte packets)
< 2.3 μ s (64-byte packets)
up to 11.9 Mpps
16 Gbps
8000 entries

Environment

Operating temperature
Operating relative humidity
Nonoperating/Storage temperature
Nonoperating/Storage relative humidity
Altitude
Acoustic

32°F to 104°F (0°C to 40°C)
15% to 95% @ 104°F (40°C)
-40°F to 158°F (-40°C to 70°C)
15% to 95% @ 140°F (60°C)
up to 10,000 ft (3 km)
Power: 0 dB no fan

32°F to 104°F (0°C to 40°C)
15% to 95% @ 104°F (40°C)
-40°F to 158°F (-40°C to 70°C)
15% to 95% @ 140°F (60°C)
up to 10,000 ft (3 km)
Power: 0 dB no fan

Electrical characteristics

Frequency
AC voltage
Current
Maximum power rating

50/60 Hz
100 - 127 / 200 - 240 VAC
.4/.3 A
22 W

50/60 Hz
100 - 240 VAC
.5 A
7.2 W

Notes

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety

UL 60950-1; IEC 60950; EN 60950

UL 60950-1; IEC 60950; EN 60950

SPECIFICATIONS

HPE 1810-24 v2 Switch (J9801A)

HPE 1810-8G v2 Switch (J9802A)

Emissions

EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4

EN 55022 Class A; CISPR 22 Class A; VCCI V-3; FCC (CFR 47, Part 15) Subpart B Class A; VCCI V-4

Immunity

ESD
Radiated
EFT/Burst
Surge
Conducted
Power frequency magnetic field
Voltage dips and interruptions
Harmonics
Flicker

IEC 61000-4-2
IEC 61000-4-3
IEC 61000-4-4
IEC 61000-4-5
IEC 61000-4-6
IEC 61000-4-8
IEC 61000-4-11
EN 61000-3-2
EN 61000-3-3

IEC 61000-4-2
IEC 61000-4-3
IEC 61000-4-4
IEC 61000-4-5
IEC 61000-4-6
IEC 61000-4-8
IEC 61000-4-11
EN 61000-3-2
EN 61000-3-3

Management

Web browser

Web browser

Notes

Use only supported genuine HPE mini-GBICs with your switch.

Use only supported genuine HPE mini-GBICs with your switch.

Services

Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

Refer to the Hewlett Packard Enterprise website at hpe.com/networking/services for details on the service-level descriptions and product numbers. For details about services, and response times in your area, please contact your local Hewlett Packard Enterprise sales office.

STANDARDS AND PROTOCOLS

(applies to all products in series)

Denial of service protection

CPU DoS Protection

General protocols

IEEE 802.1p Priority
IEEE 802.1Q VLANs

IEEE 802.3ad Link Aggregation Control Protocol (LACP)
IEEE 802.3x Flow Control

RFC 1534 DHCP/BOOTP Interoperation
RFC 2030 Simple Network Time Protocol (SNTP) v4

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

HPE 1810 Switch Series accessories

Cables

- HPE 0.5 m Multi-mode OM3 LC/LC Optical Cable (AJ833A)
- HPE 1 m Multi-mode OM3 LC/LC Optical Cable (AJ834A)
- HPE 2 m Multi-mode OM3 LC/LC Optical Cable (AJ835A)
- HPE 5 m Multi-mode OM3 LC/LC Optical Cable (AJ836A)
- HPE 15 m Multi-mode OM3 LC/LC Optical Cable (AJ837A)
- HPE 30 m Multi-mode OM3 LC/LC Optical Cable (AJ838A)
- HPE 50 m Multi-mode OM3 LC/LC Optical Cable (AJ839A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)
- HPE Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

Mounting kit

- HPE X410 1U Universal 4-post Rack Mounting Kit (J9583A)

Learn more at hpe.com/networking



Sign up for updates

★ Rate this document



© Copyright 2009–2014, 2016 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.