

OmniLink® TM-T88VI

Single-station Thermal Receipt Printer



Thermal Receipt Printer

POS

Revolutionary receipt printer with advanced connectivity and cloud support.

Connect to multiple devices simultaneously — printer can be dynamically shared by legacy POS terminals, tablets and mobile devices, as well as cloud servers

Triple-interface connectivity to future-proof growing businesses — maximum flexibility with three options, including built-in USB and Ethernet

Print from web-based applications — incorporates Epson's ePOS™ Print Technology

Designed for the cloud — leverage best-of-breed POS apps and perform remote firmware upgrades using OmniLink Merchant Services, plus utilize Server Direct Printing for online ordering

Distributed proximity-based printing — through Epson's beacon support using BLE (Bluetooth® Low Energy)¹

Easy printing from mobile devices — NFC (Near Field Communication) technology for easy pairing with your device²

Ultra fast transaction times — print speeds up to 350 mm/sec³, plus a high-speed auto cutter

Advanced paper-saving functions — top-margin and character-height reduction features help reduce paper usage by up to 49 percent⁴

Reliability you can count on — printhead life of 200 km, plus an auto cutter life of 3 million cuts⁵

Printer**Print Method** Thermal line printing**Print Speed³**350 mm/sec (13.8"/sec) max. for graphics and text;
Backward Paper Feeding function: 2 mm – 14.5 mm/sec
(0.08" – 0.6"/sec)**Print Resolution** 180 dpi**Fonts**

Font A (default): 12 x 24

Font B: 9 x 17 (including 2-dot horizontal spacing)

Column Capacity

80 mm model: 42/48/56 columns

58 mm model: 30/36/40 columns

Character Set95 Alphanumeric, 18 International, 128 x 43 Graphic
(including user-defined page); Options for customization
include Traditional/Simplified Chinese, Thai, Japanese and Korean**Barcode** UPC-A/E, Code 39/93/128, CODABAR PDF417,
QR-CODE, MaxiCode, Data Matrix, Aztec Code, Composite
Symbology, GS1-128, GS1 DataBar Omnidirectional/Truncated/
Limited/Expanded**Media Handling****Media Dimensions**80 mm: 79.5 ± 0.5 x 83 mm
3.13" ± 0.02" (width) x 3.27" (roll diameter)58 mm: 57.5 ± 0.5 x 83 mm
2.26" ± 0.02" (width) x 3.27" (roll diameter)**Thickness** 48 – 80 µm**General****Interfaces** Built-in USB, Built-in Ethernet (10/100Base-T/TX) +
UIB (Serial, Parallel, Powered USB), Bluetooth 3.0+EDR
(dedicated model)**Wireless (USB wireless dongle)** OT-WL05 (802.11 a/b/g/n,
2.4G/5G) or OT-WL02 (802.11 b/g/n, 2.4G)**Beacon (using Bluetooth Low Energy)** Beacon dongle¹
(Epson-approved dongle: Laird model BT820)**Printer Discovery** NFC (Near Field Communication)²,
Simple AP (wireless network)**Communication Protocols** ESC/POS®, ePOS Print Service
(Ethernet/Wireless), Server Direct Print (Ethernet/Wireless)**General (continued)****Network Security**Security: WEP, WPA-PSK, WPA2-PSK/EAP
WPA2-EAP: EAP-TLS, PEAP/MSCHAPv2, PEAP/TLS
Port open/close setting
IP address filtering**Printing from a Mobile Device**Wireless (802.11): iOS, AndroidTM and Windows[®] operating systems
Bluetooth: iOS, Android and Windows operating systems
mPOS Friendly Settings (default): DHCP enabled, DNS enabled,
IP printing enabled**Supported Customer Display**

DM-D30

DM-D110

ReliabilityMTBF: 360,000 hours
MCBF: 70,000,000 lines
Thermal head life: 200 km⁵
Auto cutter life: 3 million cuts⁵**Data Buffer**

Receive: 45 bytes or 4KB, selectable

User-defined: 12KB

Macro: 2KB

NV graphics: 384KB

NV user: 1KB

D.K.D. 2 drivers**Dimensions (W x D x H)**

5.71" x 7.68" x 5.83"

(145 x 195 x 148 mm)

Weight 3.5 lb (1.6 kg)**EMI Standards** FCC/ICES-003 Class A**Case Color** Epson[®] Black (EBCK), Epson White (ENN8.5)**Safety Standards** UL60950-1/CSA C22.2 No.60950-1**Options** Power supply cover, PS-180 AC adapter, one wall
hanging bracket, affixing tape and Connect-It[™] interfaces**Power Supply Voltage** 24 VDC ± 7%**Power Consumption**

Operating: Approx. 1.8 A (mean)

Standby: 0.5 W

Power Source: 24 VDC ± 7%

Software**Software and Utilities**

ePOS-Print (XML over HTTP): WEP/WPA/WPA2-Personal/Enterprise

ePOS-Display

Server Collaboration: Server Direct Print, Status notification

PHP/SQLite3

Backup/Restore: TM Utility (Windows)

OS/Language SupportMicrosoft[®] Windows (APD, OPOS, OPOS for .NET, JavaPOS)

Microsoft Windows 8.1 / iOS / Android (ePOS-Print SDK)

Mac[®] OS X[®]

Linux (CUPS, JavaPOS)

Warranty 4-year limited warranty in the U.S. and Canada**What's in the Box**OmniLink TM-T88VI printer, Thermal roll paper (starter roll for
testing), Power switch cover, Connector cover, Bottom cover
for connector cover, Roll paper guide, Screws, Setup guide, AC
adapter w/AC cord*, CD (drivers, utilities, and documentation)

* May not be included depending on the model

Eco Features

RoHS compliant

Recyclable product⁶Epson America, Inc. is a SmartWay[®] Transport Partner⁷**Ordering Information****

Model	Interfaces	Color**	Part Number
OmniLink TM-T88VI	Serial	EBCK	C31CE94061
OmniLink TM-T88VI	Serial	ENN8.5	C31CE94051
OmniLink TM-T88VI	Parallel	EBCK	C31CE94A9991
OmniLink TM-T88VI	Parallel	ENN8.5	C31CE94A9981
OmniLink TM-T88VI	Serial, Wireless	EBCK	C31CE94A9921
OmniLink TM-T88VI	Serial, Wireless	ENN8.5	C31CE94A9971
OmniLink TM-T88VI	Bluetooth	EBCK	C31CE94531

** All models have built-in USB and Ethernet interfaces with
mPOS-friendly settings as the default. EBCK: Epson Black;
ENN 8.5: Epson White

⚠ WARNING: The paper roll shipped together with this product can expose you to chemicals, including Bisphenol A and Bisphenol S, which are known to the State of California to cause birth defects or other reproductive harm.
Wash hands after handling.

For more information, go to www.P65Warnings.ca.gov

1 Requires the use of a beacon dongle connected to TM-T88VI printer via the USB-A port. Supports only Apple[®] iBeacon[™] compliant format. The Epson-approved dongle is Laird model BT820.
2 NFC tag requires use of a device that includes NFC reader, and may require additional software.
3 Speed based on using 80 mm wide media only and Epson's PS-180 power supply. Configurations not including the PS-180 will have a default print speed of 300 mm/sec.
4 Paper savings depend on the text and graphics printed on the receipt.
5 Rated printhead and cutter lives based on use of the following media only, with printer operated at room temperature and normal humidity: Model KT55FA: Papierfabrik August Koehler SE; Model PD160R: Oji Imaging Media Co., Ltd.; Model TF50KS-Y: NIPPON Paper Industries Co., Ltd.
6 For convenient and reasonable recycling options, visit www.epson.com/recycle
7 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency.

See the latest innovations from Epson Business Solutions at www.epson.com/forbusiness**Better Products for a Better Future[™]**
eco.epson.com**SmartWay[®]**
Transport Partner
Getting There With Cleaner Air**ENERGY STAR****Epson America, Inc.**
3131 Katella Ave., Los Alamitos, CA 90720**Epson Canada Limited**
185 Renfrew Drive, Markham, Ontario L3R 6G3www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON and ESC/POS are registered trademarks and Better Products for a Better Future is a trademark of Seiko Epson Corporation. OmniLink is a registered trademark and Connect-It and EPOS are trademarks of Epson America, Inc. Apple, Mac, Mac OS and OS X are trademarks of Apple Inc., registered in the U.S. and other countries. iBeacon is a trademark of Apple Inc. Android is a trademark of Google Inc. Microsoft and Windows are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2017 Epson America, Inc. Com-SS-Oct-13 CPD-C52697R1 10/24